

NEW CW 1064 nm Fiber Laser

High performance Laser with a robust fiber delivery

Licensed from FITEL



Feature

- ✓ Single mode fiber output (TEM 00)
- ✓ CW >20W
- ✓ Linearly polarized

Application

- ✓ Optical tweezers
- ✓ Frequency conversion
- ✓ LIDAR
- ✓ Solder Welding
- ✓ Material characterization

Specification

Wavelength	1064 nm	
Line width	< 0.15 nm	
Output power	> 5W	> 20W
Operation mode	CW	
Delivery fiber length	~ 2 m	
M ²	< 1.2 (TEM00)	
MFD	6.6 um (PM980)	
Output connector	FC/APC (physical contact is not available)	
Polarization	Linear	
Size	260 mm (W) X 149 mm (H) X 330 mm (D)	
Power consumption	< 150 W	
Power supply	AC 100~240V, 3A	
Control	stand-alone or PC(RS232C)	

Option

- ✓ Collimate output
- ✓ Longer delivery fiber (~ 5 m)
- ✓ Longitudinal single mode
- ✓ Customized wavelength (1040~1090nm)

OEM with Low Cost (DC input version) AVAILABLE

OXIDE

Oxide Corporation



1747-1 Makihara, Mukawa, Hokuto, Yamanashi 408-0302 JAPAN

Tel: +81-551-26-0022, Fax: +81-551-26-0033

Sales@opt-oxide.com, <http://www.opt-oxide.com>

Contents are things of 18-Jan-2018.