

# LLZN

## More Reliable Compact All-Solid-State Lithium Secondary Battery

### Feature

- ✓ Solid electrolyte with the highest lithium ion conductivity
- ✓ Promising to develop a compact all-solid-state lithium secondary battery



### Advantages

- ✓ Solid  
Unlike conventional electrolyte, LLZN is free from liquid leakage.
- ✓ Oxide  
Unlike sulfide electrolyte, LLZN does not generate toxic H<sub>2</sub>S gas with water.
- ✓ Single Crystal  
Unlike sintered powders, LLZN has no grain boundary on which Li metal electrodeposited, and it causes a short circuit.

### Specification

Item	Specification
Material	$\text{Li}_{6.5} \text{La}_3 \text{Zr}_{1.5} \text{Nb}_{0.5} \text{O}_{12}$
Diameter	5 mm ~ 7 mm $\varphi$
Rod length	Up to 50 mm
Thickness	1.0 mm, 0.5 mm (as standard)
Surface finished	As Sliced (as standard)

**OXIDE**



**OXIDE Corporation**

1747-1 Maginohara, Mukawa, Hokuto, Yamanashi 408-0302 JAPAN  
Tel: +81-551-26-0022, Fax: +81-551-26-0033



[Sales@opt-oxide.com](mailto:Sales@opt-oxide.com)



<https://www.opt-oxide.com>



**Oxide Yamanashi**