

CW 1064 nm Fiber Laser

High performance Laser with a robust fiber delivery

Licensed from FITEL



Feature

- ✓ Single mode fiber output (TEM 00)
- ✓ CW >20W
- ✓ Linearly polarized

Application

- ✓ Optical tweezers
- ✓ Frequency conversion
- ✓ LIDAR
- ✓ Solder Welding
- ✓ Material characterization

Specification

Wavelength	1064 nm		
Line width	< 0.15 nm		
Output power	> 5W	> 10W	> 20W
Operation mode	CW		
Delivery fiber length	~ 2.5 m.		
M ²	< 1.2 (TEM00)		
MFD	6.6 um (PM980)		
Output connector	FC/APC (physical contact is not available)		
Polarization	Linear		
Size	260 mm (W) X 149 mm (H) X 330 mm (D)		
Power consumption	< 150 W		
Power supply	AC 100~240V, 3A		
Control	stand-alone or PC(RS232C)		

Option

- ✓ Collimate output
- ✓ Longer delivery fiber (~ 10 m)
- ✓ Longitudinal single mode
- ✓ Customized wavelength (1040~1090nm)

OEM with Low Cost (DC input version) AVAILABLE

OXIDE

Oxide Corporation



1747-1 Makihara, Mukawa, Hokuto, Yamanashi 408-0302 JAPAN

Tel: +81-551-26-0022, Fax: +81-551-26-0033

Sales@opt-oxide.com, <https://www.opt-oxide.com>

Contents are things of 10-Sep.-2020.

PM CW1064 Fiber Laser (OEM Version)

Licensed from FITEL



Feature

- ✓ Simple configuration
- ✓ Cost effective
- ✓ PM 980 delivery (TEM00)
- ✓ Relatively narrow linewidth
- ✓ Good combination with the wavelength conversion device

Application

- ✓ Light source for Frequency conversion
- ✓ Solder welding
- ✓ Inspection (optical tweezer)
- ✓ Spectroscopic analysis

Specification (LM164)

Wavelength	1064 nm
Line width	< 0.15 nm
Output power	5W, 10W, 20 W
Operation mode	CW
Delivery fiber length	~ 2.5 m
M ²	< 1.2 (TEM00)
MFD	6.6 μm (PM980)
Output connector	FC/APC (physical contact is not available)
Polarization	Linear
Size	200 mm X 100 mm X 16 mm
Required power supply (not included in standard version)	DC: 12 V, 10.5 A (for 20W version)

Accessories

- ✓ Collimate output
- ✓ Heat sink
- ✓ DC power supply
- ✓ Customized wavelength (1040~1090nm)
- ✓ Longer delivery fiber (~ 10 m)

OXIDE

Oxide Corporation



1747-1 Makihara, Mukawa, Hokuto, Yamanashi 408-0302 JAPAN

Tel: +81-551-26-0022, Fax: +81-551-26-0033

Sales@opt-oxide.com, <https://www.opt-oxide.com>

Contents are things of 28-Nov.-2019.